

DB Bolt & Nut



Dutch Barrier's Bolt & Nut set is a small but essential part of the Dutch Barrier system. Made from hardened steel and designed exclusively for our product line, each bolt is identical across all barrier types—ensuring consistent connections and simplifying handling on site. Unlike off-the-shelf hardware, these custom fasteners are built for durability and reliability in demanding event environments.

- a state of the art aluminium barrier system, built for fast setup and optimised crowd control solutions -

About

Dutch Barrier's founders and partners boast over 50 years of experience in high-end manufacturing, layout design, and crowd control solutions. We saw an opportunity to start afresh with an entirely new stage barrier design, preserving the best features and improving upon them where possible.

Why

We believe in quality, safety, and creating an unforgettable experience. The safer an audience is, the more comfortable it will feel at your event.

How

We achieve quality and safety by leveraging 50-plus years of combined original creators' experience to reinvent the to date world's best barrier system from the ground up, making it accessible to anyone who might be in the market for such a system, either to rent or to buy.


What

Dutch Barrier® is a state-of-the-art lightweight aluminium barrier system offering an innovative combination of straights, special sections and storage solutions. Create ingenious crowd control solutions, enjoy quick setups and enhanced handling, and benefit from an equal footprint for every dolly during transport or storage.

Oh, and there's one more thing...

Dutch Barrier® is not just a brand. It's a state-of-the-art engineering company where customer support is an integral part of the mission rather than being hidden behind the impersonality of an online promise.

More information: info@dutchbarrier.nl Rental & Sales: info@duchtbarrier.services



Technical Specs

- Bolt of 8.8-grade steel, precision turned with thread rolled to increase strength to 10.9-grade This process reduces thread wear, ensuring that if a nut is misaligned, the nut will fail before the bolt. Features a 10mm internal hex socket and is compatible with standard M12 nuts, suitable for tightening with a wrench and Allen key.
- Stored and travel per 50 units in a plastic box
- Weight 180 g